

OVERVIEW



1. 2x USB 2.0	8. USB 3.2 Gen 2
2. 2x USB 3.2 Gen 1	9. 2x USB 3.2 Gen 1
3. Headphone (3.5mm)	10. Ethernet (RJ-45)
4. Power button	11. 6x Audio line-out (3.5mm)
5. Microphone (3.5mm)	12. Optional ports on expansion cards
6. 4x USB 2.0	13. Power connector
7. USB-C 3.2 Gen 2	

PERFORMANCE

Processor

Processor Family

10th Generation Intel® Core™ i5 / i7 / i9 Processor

Processor^[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i7-10700K	8	16	3.8GHz	5.1GHz	16MB	DDR4-2933	Intel UHD Graphics 630
Core i7-10700KF	8	16	3.8GHz	5.1GHz	16MB	DDR4-2933	-
Core i7-11700K	8	16	3.6GHz	5.0GHz	16MB	DDR4-3200	Intel UHD Graphics 750
Core i9-10850K	10	20	3.6GHz	5.2GHz	20MB	DDR4-2933	Intel UHD Graphics 630
Core i9-10900K	10	20	3.7GHz	5.3GHz	20MB	DDR4-2933	Intel UHD Graphics 630
Core i9-10900KF	10	20	3.7GHz	5.3GHz	20MB	DDR4-2933	-
Core i9-11900K	8	16	3.5GHz	5.3GHz	16MB	DDR4-3200	Intel UHD Graphics 750
Core i9-11900KF	8	16	3.5GHz	5.3GHz	16MB	DDR4-3200	-

Notes:

- 1. Intel UHD Graphics 630 in processor is disabled

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Pro 64
- No operating system

Graphics

Graphics^[1]

Graphics	Type	Memory	Connector	Max Resolution	Key Features
AMD Radeon™ RX 6800XT	Discrete	16GB GDDR6	1x HDMI® 2.1, 2x DP 1.4, 1x USB-C 3.2 Gen2	7680*4320@120Hz (HDMI), 7680x4320@60Hz(DP)	DirectX® 12
NVIDIA® GeForce® RTX™ 2060 CD	Discrete	6GB GDDR6	1x HDMI 2.0b, 3x DP 1.4	4096x2160@60Hz(HDMI), 7680x4320@60Hz with DSC(DP)	DirectX 12
NVIDIA GeForce RTX 2070 CD	Discrete	8GB GDDR6	1x HDMI 2.0b, 3x DP 1.4	7680x4320@60Hz(DP)	DirectX 12 VR ready
NVIDIA GeForce RTX 2070 SUPER	Discrete	8GB GDDR6	1x HDMI 2.0b, 1x USB Type-C Gen 2, 3x DP 1.4	7680x4320@60Hz(DP)	DirectX 12 VR ready
NVIDIA GeForce RTX 2080 SUPER	Discrete	8GB GDDR6	1x HDMI 2.0b, 3x DP 1.4	7680x4320@60Hz(DP)	DirectX 12 VR ready
NVIDIA GeForce RTX 3060	Discrete	12G GDDR6	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI), 7680x4320@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3060 Ti	Discrete	8G GDDR6	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI), 7680x4320@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3070 Ti	Discrete	8G GDDR6	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI); 7680x4320@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3070	Discrete	8G GDDR6	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI); 7680x4320@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3080 Ti	Discrete	12G GDDR6	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI); 7680x4320@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3080	Discrete	10G GDDR6X	3x DP 1.4a, 1x HDMI 2.1	7680x4320@60Hz(HDMI); 7680x4320@60Hz(DP)	DirectX 12

Notes:

1. The information of integrated graphics are not applicable for the models without integrated graphics (for the details, please refer to processor section)

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays via discrete graphics ports** (DP, HDMI, USB-C 3.2 Gen2, and DVI)

Notes:

1. Ports may vary by the discrete graphics.

Chipset

Chipset

Intel Z490 chipset

Memory

Max Memory^[1]

Up to 128GB DDR4-2933

Memory Slots

Four DDR4 UDIMM slots, dual-channel capable

Memory Type^[2]

- DDR4-3200
- DDR4-3200, Armor
- DDR4-3600, RGB Armor, XMP

Memory Protection

Non-ECC

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
2. Installed memory is actually 3200MHz or 3600MHz, but may run at 2933MHz depending on the memory support capability of processor

Storage

Storage Support

Up to 4 drives, 2x 3.5" HDD + 2x M.2 SSD

- 3.5" HDD up to 2TB each
- M.2 SSD up to 1TB each

Storage Type

Disk Type	Interface	RPM	Security
3.5" SATA HDD	SATA 6Gb/s	7.2K	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4	-	-

RAID

RAID 0/1/5 support

Removable Storage

Optical

- DVD burner (DVD±RW), SATA 1.5Gb/s, slim (9.0mm)
- None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC892 codec

Power Supply

Power Supply

Power	Type	Efficiency	Key Features
550W	Fixed	88%	220V
650W	Fixed	90%	100V - 240V
850W	Fixed	90%	100V - 240V

DESIGN

Input Device

Keyboard

- Lenovo Calliope Keyboard (USB connector), black
- No keyboard

Mouse

Lenovo Calliope Mouse (USB connector), black

Mechanical

Form Factor

Tower (34L)

Dimensions (WxDxH)

211 x 450 x 483 mm (8.3 x 17.7 x 19 inches)

Weight

12.5 kg (27.6 lbs)

Case Color

Raven black

Chassis

- Transparent side cover
- Transparent side cover and inner decorate cover

Bays

- 4x 2.5" disk bay
- 2x 3.5" disk bay

Expansion Slots

- Three PCIe 3.0 x1
- Two PCIe 3.0 x16
- Three M.2 slots (one for WLAN, two for SSD)

Cooling System (Fan&Cooler)

- (Optional) 3x front system fan with ARGB, 1x rear system fan with ARGB
- (Optional) 3x front system fan with ARGB, 1x rear system fan with ARGB, 2x top system fan with ARGB
- (Optional) 150W side flow Air-Cooler or 200W Liquid-Cooler
- (Optional) 1x front system fan, 1x rear system fan for airflow or liquid

System Lighting

- (Optional) Internal ambient lighting
- Legion OY iconic LED

Others

Carry handle

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, 1x RJ45

WLAN + Bluetooth®

802.11ax 2x2 Wi-Fi + Bluetooth 5.0, M.2 Card

Ports^[1]

Rear Ports^[2]

- 4x USB 2.0
- 2x USB 3.2 Gen 1
- 1x USB 3.2 Gen 2
- 1x USB-C 3.2 Gen 2 (support data transfer and 5V@3A charging)
- 1x Ethernet (RJ-45)
- 1x line-in (blue)
- 1x line-out / front output (green)
- 1x microphone in (pink)
- 1x centre and subwoofer combine output (orange)
- 1x side surround output (grey)
- 1x rear surround output (black)
- 1x power connector

Top Ports

- 2x USB 2.0
- 2x USB 3.2 Gen 1
- 1x headphone (3.5mm)
- 1x microphone (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s
2. For video ports on discrete graphics, please see graphics section

SECURITY & PRIVACY

Security

BIOS Security

- Administrator password
- Power-on password

SERVICE

Warranty

Base Warranty

- 1-year mail-in service
- 1-year depot service
- 1-year limited onsite service
- 2-year depot service

ENVIRONMENTAL

Operating Environment

Temperature

Storage: -40°C (-40°F) to 60°C (140°F)

Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

- Operating: -15.2 m (-50 ft) to 3048 m (10,000 ft)
- Storage: -15.2 m (-50 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0 (on some models)
- ErP Lot 3
- RoHS compliant

